

In the Claims

Please amend claims 1 and 8 so that the claims read as follows:

1. (Currently Amended) A method of supplying substrates to a processing tool, comprising:
 - providing a plurality of load ports each having a mechanism adapted to open a substrate carrier;
 - providing a factory exchange location at which substrate carriers are exchanged with a substrate carrier transport device while the substrate carriers are in motion and being transported by the substrate carrier transport device;
 - providing a carrier handler having an end effector adapted to contact a substrate carrier, and disengage the substrate carrier from the substrate carrier transport device while the substrate carrier is in motion and being transported by the substrate carrier transport device ~~the carrier handler being adapted to transport substrate carriers between the factory exchange location and the plurality of load ports;~~
 - receiving a first plurality of substrate carriers at the factory exchange location from the substrate carrier transport device; and
 - for each of the first plurality of substrate carriers:
 - transporting the substrate carrier from the factory exchange location directly to a respective one of the plurality of load ports;
 - docking and opening the substrate carrier at the respective load port;
 - undocking and closing the substrate carrier at the respective load port;
 - transporting the substrate carrier from the respective load port directly to the factory exchange location;
 - and

BEST AVAILABLE COPY

returning the substrate carrier to the substrate carrier transport device while the substrate carrier transport device is in motion.

2. (Original) The method of claim 1, wherein the substrate carriers are single substrate carriers.

3. (Original) The method of claim 1, wherein the step of providing a plurality of load ports comprises providing two stacks of load ports.

4. (Original) The method of claim 3, wherein the carrier handler moves the substrate carriers only within an envelope defined by footprints of the two stacks of load ports.

5. (Original) The method of claim 1, wherein the docking of each substrate carrier occurs simultaneously with opening of the respective substrate carrier.

6. (Original) The method of claim 1, wherein the factory exchange location and the load ports have substantially the same footprint.

7. (Original) The method of claim 1, wherein the factory exchange location is at a height greater than respective heights of all of the load ports.

8. (Currently Amended) A substrate loading station for a processing tool, comprising:

a first plurality of load ports operatively coupled to the processing tool and each having a mechanism adapted to open a substrate carrier;

a factory exchange location at which substrate carriers are exchanged with a substrate carrier transport device while the substrate carriers are in motion and being transported by the substrate carrier transport device;

a carrier handler having an end effector adapted to contact a substrate carrier and disengage the substrate carrier from the substrate carrier transport device while the substrate carrier is in motion and being transported by the substrate carrier transport device, the carrier handler being adapted to transport substrate carriers between the substrate carrier transport device ~~factory exchange location~~ and the first plurality of load ports; and

a controller in communication with the carrier handler, load ports, and the factory exchange location, the controller being configured to control transporting a substrate carrier from the factory exchange location directly to a respective one of the plurality of load ports, docking and opening the substrate carrier at the respective load port, undocking and closing the substrate carrier at the respective load port, transporting the substrate carrier from the respective load port directly to the factory exchange location, and returning the substrate carrier to the substrate carrier transport device while the substrate carrier transport device is in motion.

9. (Original) The substrate loading station of claim 8, wherein the substrate carriers transported by the carrier handler are single substrate carriers.

10. (Original) The substrate loading station of claim 8, further comprising:

a second plurality of load ports, the second plurality of load ports being spaced apart from and to a side of the first plurality of load ports.

11. (Original) The substrate loading station of claim 10, wherein the carrier handler is adapted to move vertically in a space between the first and second pluralities of load ports.

12. (Original) The substrate loading station of claim 11, wherein the carrier handler is adapted to move the substrate carriers only within an envelope defined by footprints of the first and second pluralities of load ports.

13. (Original) The substrate loading station of claim 8, wherein each of the load ports is adapted to open a substrate carrier simultaneously with the substrate carrier docking with the load port.

14. (Original) The substrate loading station of claim 8, wherein the factory exchange location and the load ports have substantially the same footprint.

15. (Original) The substrate loading station of claim 8, wherein the substrate carrier transport device is a conveyor.

16. (Original) The substrate loading station of claim 8, wherein the factory exchange location is at a height greater than respective heights of all of the load ports.

17. (Previously Presented) An apparatus adapted to supply substrates to a processing tool, comprising:

a substrate carrier handler adapted to transport a substrate carrier to a first load port of the processing tool, the substrate carrier handler including an end effector adapted to support the substrate carrier; and

a controller coupled to the substrate carrier handler and operative to control the substrate carrier handler such that the end effector of the substrate carrier handler disengages the substrate carrier from a substrate carrier conveyor while the substrate carrier is in motion and being transported by the substrate carrier conveyor, the controller being configured to control transporting the substrate carrier from the substrate carrier conveyor directly to the first load port, docking and opening the substrate carrier at the first load port, undocking and closing the substrate carrier at the first load port, and returning the substrate carrier directly to the substrate carrier conveyor.

18. (Previously Presented) An apparatus adapted to supply substrates to a processing tool, comprising:

a substrate carrier handler adapted to transport a substrate carrier to a first load port of the processing tool, the substrate carrier handler including:

a vertical guide;

a horizontal guide coupled to the vertical guide; and

an end effector adapted to support the substrate carrier and to move vertically relative to the vertical guide and horizontally relative to the horizontal guide; and

a controller coupled to the substrate carrier handler and operative to control the substrate carrier handler such that the end effector of the substrate carrier handler disengages the substrate carrier from a substrate carrier conveyor positioned adjacent the substrate carrier handler while the substrate carrier is in motion, the controller being configured to control transporting the substrate carrier from the substrate carrier conveyor directly to the first load port, docking and opening the substrate carrier at the first load port, undocking and closing the substrate carrier at the first load port, and returning the substrate carrier directly to the substrate carrier conveyor.

19. (Original) A method of transferring a substrate carrier, comprising:

conveying the substrate carrier on a substrate carrier conveyor positioned adjacent a substrate loading station that includes a substrate carrier handler adapted to transport the substrate carrier to a load port of a processing tool;

employing an end effector of the substrate carrier handler of the substrate loading station to disengage the substrate carrier from the substrate carrier conveyor while the substrate carrier is in motion and being transported by the substrate carrier conveyor;

transporting the substrate carrier from the substrate carrier conveyor directly to the load port;

docking and opening the substrate carrier at the load port;

undocking and closing the substrate carrier at the load port; and

returning the substrate carrier directly to the substrate carrier conveyor.

20. (Previously Presented) A method of transferring a substrate carrier to a substrate loading station, comprising:

conveying the substrate carrier on a substrate carrier conveyor positioned adjacent the substrate loading station, the substrate loading station having:

a substrate carrier handler adapted to transport the substrate carrier to a first load port of a processing tool, the substrate carrier handler including:

a vertical guide;

a horizontal guide coupled to the vertical guide; and

an end effector adapted to support the substrate carrier and to move vertically relative to the vertical guide and horizontally relative to the horizontal guide;

employing the end effector of the substrate carrier handler of the substrate loading station to disengage the substrate carrier from the substrate carrier conveyor while the substrate carrier is in motion on the substrate carrier conveyor;

transporting the substrate carrier from the substrate carrier conveyor directly to the first load port;

docking and opening the substrate carrier at the first load port;

undocking and closing the substrate carrier at the first load port; and

returning the substrate carrier directly to the substrate
carrier conveyor.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.